

Photoelectric lighting controller

# NightMatic 2000

black  
EAN 4007841 550318  
Article number 550318



Twilight switch

1000 W

1000 W max.



IP54



2 - 30 lux



energy saving

3 years

manufacturer's warranty  
steinel.de/garantie



CE



TÜV Nord Baumuster  
checked

## Function description

Automatic illumination. Photo-electric lighting controller NightMatic 2000, for controlling lighting systems for building fronts, properties, shop windows etc., automatically switches light 'ON' at dusk automatically 'OFF' again at dawn.

## Technical specifications

Dimensions (L x W x H)	37 x 74 x 99 mm	Mains power supply	230 – 240 V / 50 Hz
Manufacturer's Warranty	3 years	Switching output 1, resistive	1000 W
Settings via	Potentiometers	Switching output 1, number of LEDs / fluorescent lamps	4 pcs.
Version	black	Fluorescent lamps, uncorrected	500 VA
PU1, EAN	4007841550318	Capacitive load in $\mu\text{F}$	88 $\mu\text{F}$
Type	Photo-cell controller	Power consumption	0,8 W
Application, place	Outdoors	Technology, sensors	Light sensor
Application, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway	Twilight setting	2 – 30 lx
Colour	black	Basic light level function	No
Colour, RAL	9005	Main light adjustable	No
Includes corner wall mount	No	Twilight setting TEACH	No
Installation site	wall	Constant-lighting control	No
Installation	Surface wiring, Wall	Interconnection	Yes
IP-rating	IP54	Type of interconnection	Master/master
Ambient temperature	from -20 up to 50 °C	Interconnection via	Cable
Material	Plastic	Product category	Photoelectric lighting controller

<https://www.steinell.de>

Subject to technical modifications

12.2024 Page 1 from 2

Photoelectric lighting controller

# NightMatic 2000


black

EAN 4007841 550318

Article number 550318



## Dimension Drawing



## Circuit diagram

